

IBC Invitation

IBC 2026 - Hall 10.B40

We would like to invite you to visit KOKUSAI DENKI at IBC 2026 in Amsterdam.
We would be delighted to welcome you to our booth for live demonstrations of our latest broadcast solutions.

Booth 10.B40 | Hall 10 | 11–14 September 2026 | Amsterdam

SK-Series Elite Infrastructure	Z-Series Agile Infrastructure	DK-Series Multi-Purpose Integration/ Discrete Infrastructure	RU-2500JY Remote Control Panel
 SK-UHD7000 4K Flagship Model 4K/HD HDR ST 2110  SK-UHD7000-S2 4K-ready Model License Upgradable HD to 4K 4K/HD HDR ST 2110 - Native 4K, 3CMOS Global Shutter Sensors - UHD/HD*, HDR/SDR, BT.2020/BT.709 Simultaneous Operation - Slow-motion (License Upgradable)	 Z-HD6500-S1 4K Model 4K/HD HDR  Z-HD6500 Full HD Model Oversampled HD for Superior 1080p 4K/HD 4K/HD Cameras with 4K, 3CMOS Global Shutter Sensors - HDR/SDR, BT.2020/BT.709 Simultaneous Operation	 DK-H700 4K Multi-purpose BOX Model 4K/HD HDR - Native 4K, 3CMOS Global Shutter Sensors - UHD/HD, HDR/SDR, BT.2020/BT.709 Simultaneous Operation - Match SK/Z colorimetry 12G Optical Fiber Output Model Available	 RU-2500JY Remote Control Panel The RU-2500JY features 82 mm slim width despite having a 3.5-inch Quick response LCD touch panel, backlit controls, USB memory slot for saving or sharing camera scene file data and IP connectivity with Power over Ethernet (PoE).

In addition, we will showcase the products below from our group companies:

Nisshinbo Micro Devices		LINEAR DENKI
		
NJT8402 is a compact Ka-band 5W transceiver integrating a BUC and LNB in a single unit. Featuring a 29 to 30 GHz TX band and a switchable 17.7–20.2 GHz RX band for flexible system configuration. Suitable for a wide range of satellite communication applications.	NJR8501 is a Q-band LNB featuring a <u>switchable frequency band covering 38 to 42 GHz.</u> Designed for gateway stations, this receiver covers 38–42 GHz, supports wideband reception, and enables simultaneous dual-band reception. Its low NF ensures high-quality communications.	Broadcast FM Radio Transmitter 1.2 to 60 kW outpower. Featuring high-efficiency performance along with comprehensive monitoring and signal-processing capabilities

LIVE DEMOS:

SK-UHD7000 & CU-UHD7000-S4 & RU-2500JY - ST2110 Remote Production.

The KOKUSAI DENKI **SK-UHD7000** with **CU-UHD7000-S4** CCU which is fitted with SDI and IP / ST-2110 interfaces and the new **RU-2500JY** remote control panel, to be demonstrated as a key workflow element of KOKUSAI DENKI's 4K MoIP ST2110 remote production camera system.

Z-HD6500-S1 cost effective and streamlined UHD/HD production camera system.

The **Z-HD6500-S1** features the same 2/3-inch UHD-native Global shutter sensors as the SK-UHD7000. Its RGB 3-chip technology, with 8.3 million effective pixels per sensor with full range BT-2020 Prism resulting in sharp, vibrant images with minimal noise, outstanding color fidelity and remarkable sensitivity.

SK-UHD7000 QUARTZ Wireless Camera System - ST2110 Remote Production.

Fully remote-controllable UHD wireless Camera with a fully integrated Domo 4K HEVC COFDM wireless video transmission system with Mesh Technology Intercom and ST2110 interface for remote production.

DK-H700 & KXWELL Robotic Camera system.

DK-H700 4K Box Camera is a compact POV solution based on SK-UHD7000, delivering matching UHD image quality for broadcast, professional AV, theatres, parliaments, and government applications.

More info: www.kokusaidenki.eu